

## Technical specs

Version	1.6 Petrol 4x2	1.6 Petrol 4x2 CA	1.6 Petrol 4x4	2.0 4x2	2.0 4x4
<b>Engine</b>					
Displacement (cc)	1586	1586	1586	1956	1956
Displacement (l)	1.6	1.6	1.6	2	2
Engine timing control	Toothed belt	Toothed belt	Toothed belt	Toothed belt	Toothed belt
Engine tappets	Hydraulic tappets	Hydraulic tappets	Hydraulic tappets	Hydraulic tappets	Hydraulic tappets
Bore x Stroke (mm)	78x83	78x83	78x83	83x90.4	83x90.4
Cylinder arrangement	In line				
Number of cylinders	4				
Fuel supply type	MPI	MPI	MPI	D Common Rail	D Common Rail
Timing system type	2ACT				
Fuel	Petrol	Petrol	Petrol	Diesel	Diesel
Engine features	Aspirated	Aspirated	Aspirated	Turbo-charged	Turbo-charged
Engine family	SZK	SZK	SZK	B Ds	B Ds
Number of valves per cylinder	4				
Compression ratio	10.5	10.5	10.5	16.5	16.5
Transmission	Manual	Automatic	Manual	Manual	Manual
Transmission family	SZK				
No. gears	5	4	5	6	6
Clutch control	Dry disc with engagement spring				
Traction	Front	Front	4x4 with self-locking differential electronically controlled	Front	4x4 with electronically controlled self-locking differential
Emission standard	Euro 5				

<b>Performance and fuel consumption</b>					
Acceleration 0 - 100 km/h (secs)	10.7	12.3	11.5	10.5	11.2
Combined consumption (l/100 km)	6.2	7.2	6.5	4.9	5.5
Urban consumption (l/100 km)	7.9	9.2	8.2	6.2	7
Extra-Urban consumption (l/100 km)	5.2	5.9	5.5	4.2	4.6
Max torque (rpm)	4400	4400	4400	1500	1500
Nm torque	156	156	156	320	320
kgm torque	15.9	15.9	15.9	32.6	32.6
CO <sub>2</sub> emissions (g/km)	143	165	149	129	143
Max power (rpm)	6000	6000	6000	3500	3500
Max power (HP)	120	120	120	135	135
Max power (kW)	88	88	88	99.2	99.2
Top speed (km/h)	185	175	175	190	180
<b>Brake system, wheels, suspensions, electronics</b>					
Front: Ø mm	D 280				
Rear: Ø mm	D 280				
Brake servo: Ø mm	10"				
Front suspensions	Independent McPherson type wheels				
Rear suspensions	Torsion beam				
Tyres	205 / 60 R16				
Battery capacity (Ah)	36	36	36	60	60
Steering type	pinion electric				
Steering diameter (m)	11				
<b>Dimensions</b>					
Max height when empty (mm)	1605	1605	1620	1605	1620
Front track: Ø mm	1500	1500	1495	1500	1495
Rear track: Ø mm	1495	1495	1495	1495	1495
Width (mm)	1755	1755	1755	1755	1755
Length (mm)	4115	4115	4115	4115	4115
No. of seats	5	5	5	5	5
No. of doors	5	5	5	5	5
Wheelbase size (mm)	2500	2500	2500	2500	2500
Minimum height from ground (standard A) (mm)	175	175	190	175	190
Luggage capacity (dm <sup>3</sup> )	270/670	270/670	270/670	270/670	270/670

<b>Weights-capacities</b>					
Weight in running order (kg)	1215	1230	1275	1360	1425
Towable weight	1200				
Fuel tank capacity	50				